



表：MJT-Cシリーズ寸法表

単位：mm

型番	軸穴径	A	L	W	B	C*	G	F	M	ねじ締付トルク (N・m)
MJT-14C	3~5 6~7	14	7	22	6	1	4 5	3.5	M2 M1.6	0.5 0.25
MJT-20C	4~8 9.525~11	20	10	30	8	1	6.5 7.5	5	M2.5 M2	1 0.5
MJT-30C	6~12 14~16	30	11	35	10	1.5	10 11	5.5	M4 M3	2.5 1.5
MJT-40C	8~20 22~25	40	25	66	12	2	14 15.75	8.5	M5 M4	4 2.5

*C寸法をつけた状態で使用してください。

型番	標準軸穴径 D ₁ ・D ₂																								
	3	4	4.5	5	6	6.35	7	8	9.525	10	11	12	14	15	16	18	19	20	22	24	25				
MJT-14C	●	●	●	●	●	●	●																		
MJT-20C		●	●	●	●	●	●	●	●	●	●														
MJT-30C					●	●	●	●	●	●	●	●	●	●	●										
MJT-40C								●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

表：MJT-Cシリーズ性能表

型番	最大軸穴径 (mm)	常用トルク (N・m)	最大トルク (N・m)	最高回転数 (min ⁻¹)	慣性モーメント (kg・m ²)	静的ねじりばね定数 (N・m/rad)	許容偏心 (mm)	許容偏角 (°)	許容エンドプレイ (mm)	質量 (g)
MJT-14C	7	2	4	45000	1.9×10 ⁻⁷	22	0.1	1.0	+0.6 0	6.2
MJT-20C	11	5	10	31000	1.0×10 ⁻⁶	55	0.1	1.0	+0.8 0	16
MJT-30C	16	12.5	25	21000	6.0×10 ⁻⁶	130	0.1	1.0	+1.0 0	42
MJT-40C	25	17	34	15000	3.6×10 ⁻⁵	1200	0.1	1.0	+1.2 0	130